## data sheet Nr. 6000

COLDEC

Talhoutweg 17

8171 MB Vaassen, The Netherlands

Phone +31 (0)578 578525 Fax +31 (0)578 577934

e-mail info@coldec.nl

## **ROLPLAST**

PRODUCT DESCRIPTION	Ready-to-use multicolour textured paint for interior use.	
PRODUCT CHARACTERISTICS	Colours Glossrate Odour	Multicolour semi-gloss mild
APPLICATION	Surfaces must be thoroughly dry, clean, free of dust and grease. Any defects should be repaired. Inadequate surfaces, with eg. nicotine or water stains, should be pre-treated with a primer.  Stir firmly before application. It is recommended to apply Rolplast with a lamb's wool roller in two thin and even layers. The roller should be made slightly wet before application, The first strikes of Rolplast should be made on a piece of cardboard to make sure the material is well-absorbed in the roller. Use the roller to apply Rolplast as close as possible to the corners and edges and spread out the material with a brush. For larger surfaces it is recommended to apply Rolplast area by area.  Under normal conditions (humidity 65%, temp. +20° C) the second layer can be applied wet on wet 30 minutes after the first layer. In case the temperature is substantially lower or the humidity substantially higher it is advised to increase the waiting time before application of the second layer.	
TECHNICAL PROPERTIES	Binder Solvent Pigment Specific weight Adhesion Scratch resistance Water resistance Application temperature Drying time Consumption Maintenance	vinylacetate-vinylversatate. water colourflakes type OO size 0,5 1,25 g/cm³ excellent excellent good at least 5° C 6-10 hours (humidity 65%, temp.+20° C), fully cured after 48 hours ± 600 gr/m². Determine exact consumption by making a test-surface at the project. normal detergent
CLEANING TOOLS	Immediately rinse tools with water after application.	
SHELF LIFE	Closed in original packaging under normal conditions (between +5°C and +20°C) at least 12 months after production date. Limited tenability after opening.	
STORAGE	Dry and cool, but frost-free.	